

SHEET MEMBRANES-SHOWER PAN, CRACK ISOLATION, SOUND REDUCTION



Compotite

Composeal Shower Pan

BLUE PVC
SHOWER PAN MEMBRANE

- ◆ From the Makers of the Original Shower Pan Membrane in 1938
- ◆ Meets and Surpasses ASTM D4551
- ◆ Flexible Waterproofing for Custom Tiled Showers, Baths, Fountains, Roof Decks, Terraces, Exterior Stairs & Walkways
- ◆ Can Be Easily Formed to Fit Any Dimensions or Drain Locations
- ◆ Manufactured in 30 & 40 mil Thicknesses - 4, 5 & 6 Foot Widths in 50 or 100 Foot Rolls

Composeal Shower Pan

GREY PVC
SHOWER PAN MEMBRANE

- ◆ 50% Recycled Content 
- ◆ Economically Priced
- ◆ Available in PALLETS ONLY - 15 rolls per pallet
- ◆ Meets and Surpasses ASTM D4551
- ◆ Manufactured in 40 mil Thicknesses - 5 & 6 Foot Widths
- ◆ 100 Foot Rolls

Composeal *GOLD*

CRACK ISOLATION
& WATERPROOF MEMBRANE

- ◆ Superior Double-Protection Isolates Common Shrinkage Cracks Found in Residential & Commercial Construction From Telegraphing to Finished Surface - Prevents water damage & moisture migration
- ◆ Meets and Surpasses ANSI A118.10 and ANSI A118.12 Standard for Crack Isolation Membranes
- ◆ Significant Labor Cost Savings with Fast & Quality Consistent Installation - Excellent Bonding Strength
- ◆ 40 mil Bonded Membrane - Ready to Tile

Composeal *WHITE GOLD*

SOUND REDUCTION
MEMBRANE

- ◆ Controls Sound Transmission in Vertical Construction for High Quality Thin-Set Tile Installations
- ◆ Provides Additional Crack Isolation and Waterproofing
- ◆ Sound Rating of IIC 66 and STC 66
- ◆ 50 mil Bonded Membrane - Ready to Tile

Compotite Corporation • 355 Glendale Blvd. Los Angeles, CA 90026
Tel: 800-221-1056 Fax: 800-334-3940 www.compotite.com

Call or Visit our Website to Find the Nearest Compotite Supplier



LIQUID APPLIED WATERPROOFING & CRACK ISOLATION MEMBRANES



LIQUID APPLIED WATERPROOFING
& CRACK ISOLATION MEMBRANE

- Approved as a Liquid Applied Shower Pan - Under Thick Bed Mortar or Directly Under Surface Tile - Ready to Tile
- Exceeds ANSI 118.10 & ANSI 118.12
- No Reinforcing Fabric Required
- Easy Installation - Apply with Trowel, Airless Sprayer, Paint Brush or Roller



RAPID SETTING
LIQUID APPLIED WATERPROOFING
& CRACK ISOLATION MEMBRANE

- Flood Test in 4-6 Hours
- Exceeds ANSI 118.10 and ANSI 118.12
- No Reinforcing Fabric Required
- Easy Installation - Apply with Trowel, Airless Sprayer, Paint Brush or Roller



HIGH PERFORMANCE
LIQUID APPLIED WATERPROOFING
& CRACK ISOLATION MEMBRANE

- Maximum Durability for Heavy Duty Construction
- Ideal for Commercial Steam Rooms
- Exceeds ANSI 118.10 and ANSI 118.12
- Formulated to be Used With Reinforcing Fabric Throughout
- Easy Installation - Apply with Trowel, Airless Sprayer, Paint Brush or Roller



LIQUID APPLIED
CRACK ISOLATION MEMBRANE

- One Coat & Done - Crack Isolation up to 3/8"
- Over 1,000% Elongation!
- Exceeds High Performance ANSI 118.12 Standard
- Easy Installation - Apply with Trowel, Paint Brush or Roller
- Adheres to All Common Surfaces
- Low VOC



355 Glendale Blvd. Los Angeles, CA 90026
Tel: 800-221-1056 Fax: 800-334-3940
www.compotite.com



Call or Visit our Website to Find the Nearest Compotite Supplier