

SAFETY DATA SHEET

Revision Date: 08-18-2017 Supersedes: None

SECTION 1: IDENTIFICATION	N OF THE PRODU	CT AND SUPPLIER		
PRODUCT INFORMATION				
PRODUCT:	Aqua Shell Rapid Se	et		
PRODUCT DESCRIPTION:	Coating			
INTENDED USE:	Coating			
PRODUCT IDENTIFIER:	843134PM			
COMPANY INFORMATION				
Company:	Compotite			
Street Address:	730 Mooney Street, E	Bartow, Florida 33830		
Phone:	1-800-552-6225			
Medical Emergency Phone Number (24 Hours):	1-888-853-1758			
Transport Emergency Phone Number (CHEMTREC):	1-800-424-9300			
SECTION 2: HAZARDS IDEN	ITIFICATION			
GHS Classification:	This product is not c	lassified as hazardous under (GHS criteria.	
GHS Precautions:				
Safety Precautions:	No special precautio		Please read the entire Safety Data S	Sheet for other information
First Aid Measures:	IF IN EYES: Use an ey IF ON SKIN: Wash wi	e wash to remove chemical for th soap and water.	edical attention if symptoms develom the eye. n airborne exposure if any symptor	
SECTION 3: COMPOSITION	INFORMATION O	N INGREDIENTS		
Chemical Name:	CAS #:	PERCENT:	Classification:	Note
*This product contains one or mormaterial is encapsulated within the dusting and exposure may occur. This product, this sulfor exposure. This product contains product. As such, it is considered to compliance requirements of 29CF.	e product and will not This product contains to bstance is encapsulate s crystalline silica. As po to be inextricably boun	present an exposure risk. Onc titanium dioxide, which is haz ed within the product. As such rovided, and during normal u	te the product has reached its final ardous when present as an airborn , it is considered to be inextricably se of this product, the crystalline si	I state and is abraded or disturbed, ne dust. As provided, and during bound, and not readily available lica is encapsulated within the
Unlisted ingredients are not 'hazar are not found on the Canadian Wo				Standard (29 CFR 1910.1200) and/or n 8 for exposure limit guidelines.
SECTION 4: FIRST AID MEA	SURES			
IF IN EYES:	Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.			
IF ON SKIN:	Wash with soap and water. Get medical attention if irritation develops or persists.			
IF INHALED:	Remove to fresh air. Call a physician if symptoms persist.			
IF SWALLOWED:		-	symptoms develop. Provide medic aterial into the lungs potentially ca	•
SECTION 5: FIRE FIGHTING	MEASURES			
EXTINGUISHING MEDIA:	Use water spray, foar	m, dry chemical or carbon dio	xide.	
UNUSUAL FIRE AND EXPLOSION HAZARDS:	There is a possibility containers. Material		containers when heated. Water sp	ray may be used to cool the



SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed equipment.	to products of combustion should	wear selfcontained breathing apparatus and full protective
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, C	arbon monoxide	
SECTION 6: ACCIDENTAL R	RELEASE MEASU	JRES	
SPECIAL PROTECTION:	No adverse health effects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this SDS.		
METHODS FOR CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.		
Transport Emergency Phone Number (CHEMTREC):	1-800-424-9300		
SECTION 7: HANDLING AN	D STORAGE		
Handling:	No special handli when in contact v	•	s product contains an ingredient that may release formaldehyde
Storage:	Store in a cool, dr	y place.Protect from freezing.	
Consult the Technical Data Sheet	for specific storage	instructions.	
SECTION 8: EXPOSURE CO	NTROLS/PERSO	NAL PROTECTION	
EXPOSURE LIMITS:			
Chemical Name:	Note:	ACGIH EXPOSURE LIMITS:	OSHA PEL
Calcium carbonate	* (see below)	No data available.	15 mg/m3 TWA
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
material is encapsulated within th	ne product and will r	not present an exposure risk. Once	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the the product has reached its final state and is abraded or disturbed,
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered t	re materials that ma ne product and will r This product contai obstance is encapsu ns crystalline silica. A to be inextricably bo	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once in stitanium dioxide, which is hazalated within the product. As such, is provided, and during normal us bund, and not readily available for	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain	re materials that ma ne product and will r This product contai obstance is encapsu ns crystalline silica. A to be inextricably bo FR1910.1053 or 1926.11	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once in stitanium dioxide, which is hazalated within the product. As such, is provided, and during normal us bund, and not readily available for	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the e the product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available e of this product, the crystalline silica is encapsulated within the
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered t compliance requirements of 29CF	re materials that ma ne product and will r This product contai abstance is encapsu as crystalline silica. A to be inextricably bo R1910.1053 or 1926.11	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once in stitanium dioxide, which is hazalated within the product. As such, is provided, and during normal us bund, and not readily available for	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the the product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the
*This product contains one or mor material is encapsulated within th dusting and exposure may occur.' normal use of this product, this su for exposure. This product contain product. As such, it is considered t compliance requirements of 29CF ENGINEERING CONTROL METH	re materials that ma he product and will r This product contai histance is encapsu his crystalline silica. A to be inextricably be 181910.1053 or 1926.11 HODS:	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once in stitanium dioxide, which is hazalated within the product. As such, is provided, and during normal usund, and not readily available for 153.	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the the product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered t compliance requirements of 29CF ENGINEERING CONTROL METHON:	re materials that made product and will re This product contains the stance is encapsured by the stance is encapsured by the stance is encapsured by the stance of the sta	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal usund, and not readily available for 53. bitilation might be required under es when handling this product.	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the the product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered t compliance requirements of 29CF ENGINEERING CONTROL METHON: EYE PROTECTION:	re materials that made product and will rather product contains the product contains the product contains the product is crystalline silica. At the product is created by the product is creat	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal usund, and not readily available for 53. bitilation might be required under es when handling this product.	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available to of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the enormal conditions of use.
*This product contains one or mor material is encapsulated within the dusting and exposure may occur. normal use of this product, this sufor exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHODICAL VENTILATION: EYE PROTECTION: SKIN PROTECTION:	re materials that materials that materials that materials that materials product and will reproduct contains the series of the s	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once in stitanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for stitanium might be required under es when handling this product. uired. Wear chemically resistant guired. Use nitrile gloves if condition	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHODICAL VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES:	re materials that made product and will reproduct contained the product of t	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. uired. Wear chemically resistant guired. Use nitrile gloves if condition to tection required under normal coments found in OSHA's respirator	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered tompliance requirements of 29CE ENGINEERING CONTROL METHODISTITUTE EYE PROTECTION: SKIN PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION:	re materials that made product and will reproduct contained the product of t	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. uired. Wear chemically resistant guired. Use nitrile gloves if condition to tection required under normal coments found in OSHA's respirator	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Noves to prevent prolonged or repeated contact. In swarrant. Inditions of use. Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND	re materials that made product and will reproduct and will reproduct contains the stance is encapsular contains crystalline silica. At the beinextricably beinextricably beinextricably beinextricably beinextricably beinextricably and respiratory verifollowing requires the product of the prod	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. uired. Wear chemically resistant guired. Use nitrile gloves if condition to tection required under normal coments found in OSHA's respirator	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE:	re materials that made product and will reproduct contained the product of t	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Noves to prevent prolonged or repeated contact. In swarrant. Inditions of use. Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR:	re materials that made product and will reproduct and will reproduct contains the product contains are product contains and product contains are product and product contains are producted by the product of the produc	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR: ODOR:	re materials that made product and will reproduct and will reproduct contains the product contains are product contains and product contains are product and produ	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within the dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR: ODOR: ODOR THRESHOLD:	re materials that made product and will reproduct and will reproduct contains and selection of the product contains and selection of the product contains and selection of the product of	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered tompliance requirements of 29CF ENGINEERING CONTROL METHOD VENTILATION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR: ODOR: ODOR THRESHOLD: pH: FREEZING/MELTING POINT (deg.	re materials that made product and will reproduct and will reproduct contains the product contains are product contains and product contains are product and product contains are producted by the product of the produc	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact, as warrant.
*This product contains one or mor material is encapsulated within th dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered tompliance requirements of 29CF ENGINEERING CONTROL METHOUSE PROTECTION: SEYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR: ODOR: ODOR THRESHOLD: pH: FREEZING/MELTING POINT (deg. C):	re materials that made product and will reproduct and will reproduct contains the product of the produ	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact, as warrant.
*This product contains one or mor material is encapsulated within the dusting and exposure may occur. normal use of this product, this su for exposure. This product contain product. As such, it is considered to compliance requirements of 29CF ENGINEERING CONTROL METHOUSE PROTECTION: EYE PROTECTION: SKIN PROTECTION: GLOVES: RESPIRATORY PROTECTION: SECTION 9: PHYSICAL AND PHYSICAL STATE: COLOR: ODOR: ODOR THRESHOLD: pH: FREEZING/MELTING POINT (deg. C):	re materials that made product and will rather product and will rather product contains the product of	(respirable particulate matter) by be hazardous when present as a not present an exposure risk. Once institanium dioxide, which is hazalated within the product. As such, is provided, and during normal us und, and not readily available for its. bitilation might be required under es when handling this product. Luired. Wear chemically resistant guired. Use nitrile gloves if condition to the condition of the cond	TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) an airborne dust. During normal handling of the product, the eithe product has reached its final state and is abraded or disturbed, rdous when present as an airborne dust. As provided, and during it is considered to be inextricably bound, and not readily available of this product, the crystalline silica is encapsulated within the exposure. Use of this product would not subject the user to the mormal conditions of use. Investment of use, to prevent prolonged or repeated contact. In swarrant. Inditions of use, Respirators should be selected by and used

Aqua Shell Rapid Set

843134PM



UPPER EXPLOSIVE LIMIT (% in	Not established		
air):			
LOWER EXPLOSIVE LIMIT (% in air):	Not established		
VAPOR PRESSURE (mm Hg):	Not established		
VAPOR DENSITY:	Not established		
WEIGHT PER GALLON (lbs.):	10.00		
SPECIFIC GRAVITY:	1.200		
SOLUBILITY:	Not established		
OCTANOL/WATER COEFFICIENT:	Not established		
AUTOIGNITION TEMPERATURE:	Not established		
DECOMPOSITION TEMPERATURE:	Not established		
VISCOSITY:	No data available.		
SOLIDS (% by weight):	65.0		
VOC, weight percent:	Not determined		
SECTION 10: STABILITY AND	PREACTIVITY		
STABILITY:	Stable under normal conditions.		
CHEMICAL INCOMPATIBILITY:	Not established		
HAZARDOUS POLYMERIZATION:	Will not occur.		
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide		
SECTION 11: TOXICOLOGICA	L INFORMATION		
Component Toxicity / Toxicology Da	ata:		
COMPONENT NAME:	LD50/LC50		
No data available.			
This product is a mixture. Unless no	oted, the information below is based on components.		
Skin corrosion / irritation:	No irritation hazard in normal industrial use.		
Serious eye damage / irritation:	No irritation hazard in normal industrial use.		
Respiratory / skin sensitization:	No data available.		
Germ cell mutagenicity:	No data available.		
Carcinogenicity:	Contains a material that may cause cancer.		
Reproductive toxicity:	No data available.		
Specific target organ toxicity- single exposure:	No data available.		
Respiratory irritation / Narcotic effects:	No data available.		
Specific target organ toxicity- repeated exposure:	No data available.		
Target organs potentially affected by exposure:	Lungs		
Aspiration hazard:	Not an aspiration hazard.		
Medical Conditions Aggravated by Exposure:	Lung disease		
SECTION 12: ECOLOGICAL II	ECTION 12: ECOLOGICAL INFORMATION		
OVERVIEW:	No ecological information available for this product.		
MOBILITY:	No data available.		
PERSISTENCE:	No data available.		

Aqua Shell Rapid Set





BIOACCUMULATION:	No data available.
This product has not been tested for	or ecological effects. Relevant information for components is listed below:
Component:	Ecotoxicity values:
No data available.	Acute Toxicity (Fish): Acute Toxicity (Daphnia): Acute Toxicity (Algae):

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transporta	ation information.
US DOT:	NOT REGULATED
IATA·	NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS	
U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt from DSL requirements.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.
AUSTRALIA AICS:	This product contains a component that is not on the Australian Inventory (AICS).

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg, request@hbfuller.com to request an export review.

FEDERAL REPORTING

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986: Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name	CAS#	%
Titanium dioxide (Carcinogen)	13463-67-7	0.1 - 1
Quartz (Carcinogen)	14808-60-7	0.1 - 1
Carbon black (Carcinogen)	1333-86-4	0.1 - 1
4-Vinylcyclohexene (Carcinogen)	100-40-3	< 10 ppm
Nickel (Carcinogen)		< 10 ppm
Lead compounds (Carcinogen)		< 10 ppm
Ethylene glycol (Developmental toxin)	107-21-1	0.1 - 1
1-Cyclohexene, 4-vinyl- (Female reproductive toxin)	100-40-3	< 10 ppm

Aqua Shell Rapid Set

843134PM



reproductive toxin)	3 , 1 , 1 , 1	100-40-3	< 10 ppm
---------------------	---------------	----------	----------

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS. 4-Nonylphenol, branched, ethoxylated

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 08-18-2017

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING:

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by:

The Global Regulatory Department

Phone:

651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.