



FLEXIBLE VINYL CEMENT

TECHNICAL DATA

DESCRIPTION

Composeal Flexible Vinyl Cement is a clear, light bodied, fast drying solvent cement designed specifically for use in welding seams and corners of Composeal Blue and Composeal Grey Vinyl Shower Pan Liners. Composeal Flexible Vinyl Cement can be used to weld any combination of Composeal membranes.

- ◇ **Instant Contact Strength**
- ◇ **Clear, Light Bodied, Fast Drying Seam Welding Cement**
- ◇ **For Use with Any Composeal Vinyl Membranes**
- ◇ **Industrial Use Only**

CAUTIONS

Keep out of reach of children. Do not ingest. Keep away from heat, spark, open flame, other sources of ignition. Vapors may ignite explosively. Use only in well ventilated area. If not well ventilated, use forced ventilation or NIOSH approved respirator. Avoid breathing vapors, Avoid contact with the skin and eyes. Use skin and eye protection. Eye contact may cause injury. Keep container closed.

FIRST AID/EMERGENCY:

Inhalation: If ill effects from inhalation, move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.

Eye or Skin Contact: Flush with plenty of water for 15 minutes. If irritation persists, get medical attention.

Ingestion: If swallowed, do not induce vomiting. Contact physician immediately.

Contains:

Contains Methyl Ethyl Ketone (78-93-3);
Acetone (67-64-1), Tetrahydrofuran (109-99-9).

Low VOC:

Max VOC per SCAQMD1168/316A: 510 G/L

Warning:

This product can expose you to chemicals including Tetrahydrofuran, which is known to the State of California to cause birth defects, reproductive harm, and cancer. For more info, go to www.p65warnings.ca.gov.

Danger:

Highly flammable liquid & vapor. May be fatal if swallowed & enters airways. Harmful in contact with skin. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Read label carefully before using.

Shelf Life:

This product has a shelf life of two years from date on bottom of can.

Storage:

Store between 40°F - 110°F (50°C - 43°C)

For Chemical or Medical Emergencies
Call Infotrac at 800-535-5053



Approximate Linear Feet per 1 pint: 50 feet

Approximate number of joints made by pipe size per 1 pint of cement:

Pipe Size	1/2"	3/4"	1"	1-1/2"	2"	3"	4"	6"
Approx. Joints	150	100	60	45	30	20	15	5

Contact your supplier or Compotite
for additional info or assistance.

Contact us for more product information and resources
1-800-221-1056 ◇ info@compotite.com

www.compotite.com