



MULTI-PURPOSE SOLVENT CEMENT

TECHNICAL DATA

DESCRIPTION

Weld-Tite PVC Multi-Purpose Solvent Cement is a clear, medium bodied solvent cement recommended for solvent welding flexible PVC pipe and rigid fittings up to 3" diameter. Formulated to withstand the pressure and vibrations of flexible tubing. Weld-Tite PVC Multi-Purpose Cement can be used on potable water, sewer and drain waste, and vent systems.

- ◇ **Instant Contact Strength**
- ◇ **Clear, Medium Bodied Plastic Pipe Cement**
- ◇ **ABS-ABS / ABS-PVC**
- ◇ **Industrial Use Only**

CAUTIONS

Keep out of reach of children. Keep away from heat, spark, open flame, hot surfaces - No Smoking. Keep container tightly closed and cool. Take precautionary measures against static discharge. Avoid breathing vapors. Use only outdoors or in well-ventilated area. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Do not eat or drink when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wear a NIOSH approved respirator for organic solvents.

FIRST AID/EMERGENCY:

If swallowed, drink 1 or 2 glasses of water. DO NOT INDUCE VOMITING. Contact physician immediately. If on skin, remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If inhaled, move into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call physician. If in eyes, flush with water for 15 minutes. If irritation persists, get medical attention. In case of fire, use dry chemical, Co2 or foam to extinguish fire

Disposal:

Dispose of product or container in accordance with federal, state, or local regulations.

Contains:

Tetrahydrofuran (109-99-9), Methyl Ethyl Ketone (78-93-3); Cyclohexanone (108-94-1); CPVC Resin (68648-82-8); Amorphous Silica (112945- 52-5).

Low VOC:

Max VOC per SCAQMD 1168/316A or BAAQMD Method 40: 510 g/l. Meets ASTM D-2564, D-2235 and F-493.

Warning:

This product can expose you to chemicals including Tetrahydrofuran, which is known to the State of California to cause birth defects, reproductive harm, and cancer.

For more info, go to www.p65warnings.ca.gov.

Danger:

Highly flammable liquid & vapor. May be fatal if swallowed & enters airways. Harmful in contact with skin. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Read label carefully before using.

Shelf Life

This product has a shelf life of two years from date on bottom of can.

Storage:

Store below 110°F (44°C)



APPROXIMATE NUMBER OF JOINTS MADE BY PIPE SIZE PER 1 PINT OF CEMENT

Pipe Size	1/2"	3/4"	1"	1-1/2"	2"	3"	4"	6"
Approx. Joints	150	100	60	45	30	20	15	5

For Chemical or Medical Emergencies
Call Infotrac at 800-535-5053

Contact your supplier or Compotite
for additional info or assistance.